

DEVELOPMENT OF NEW STEAM METHANE REFORMING MOBILE PLANT
WITH MICRO-SCALE CATALYTIC CHANNELS

RAIS HANIZAM BIN MADON

A thesis submitted in fulfillment of the requirement for the award of the
Doctor of Philosophy of Mechanical Engineering

Faculty of Mechanical and Manufacturing Engineering
Universiti Tun Hussein Onn Malaysia

FEBRUARY 2019

DEDICATION

*Special Dedication to
Supiah Jamil@Jamin my beloved mother, you are everything to me,
Madon Jais my late beloved father, you are my inspiration,
Meine Leibe, I believe in you and me,*

*My family members that always love me,
My friends that always care for me,*

Thanks you for always giving me encouragement to complete this study.



PTTAUTHM
PERPUSTAKAAN TUNKU TUN AMINAH

ACKNOWLEDGEMENT

In the Name of Allah, the Most Gracious, the Most Merciful. I am so thankful to Allah S.W.T for giving me enough time, good health, spirit, and patience in order to complete this PhD's project. With the mercifulness of Allah, I am able to produce a lot of useful idea for this project.

I would like thank my supervisor, Assoc. Prof. Dr. Mas Fawzi bin Mohd Ali, for his continuous professional advices, useful guidance, inspiration, patience, financial aspects and enormous support in the effort to complete this project. Also, I would like to thank my co-supervisor, Prof. Dato' Ir. Dr. Abdul Wahab bin Mohammad for his advice and support during my study. I am would like to express my thankfulness to my beloved family, especially my beloved mother, Mrs. Supiah Jamil@Jamin, my beloved wife Mrs Nor Nadiah Harun, my daughter Ms Iffah Damia, my sons Rais Irfan Daniyal and Rais Iman Daa'im for their prayers, support, patience, and motivation during my study. I am also grateful to both examiners for their brilliant ideas, advices and guidance to me

I am indebted to the Faculty of Mechanical and Manufacturing Engineering, Universiti Tun Hussein Onn Malaysia (UTHM) for their facilities, opportunity as well as financial aid provided in pursuing my research. I would like to thank the Ministry of Education Malaysia for supporting my scholarship under SLAB scheme and also for supporting this research project under the Fundamental Research Grant Scheme (FRGS) Vot 1421. I would like to dedicate my appreciation to all the lecturers and associates of the Faculty of Mechanical and Manufacturing Engineering, which involved in this project with their invaluable time, guidance and advice. Without their cooperation and sacrifices, this research would not be able to be completed and published. Especially to Mr. Muhamad Khairul Ilman bin Sarwani, Mr. Mzahar bin Abd. Jalal, Mr Asrul bin Bosiran and Dr. Shahrul Azmir bin Osman.

ABSTRACT

The search for clean alternative energy sources is vital to feed the ever-increasing world energy consumption. It is widely accepted that hydrogen is the cleanest and abundant energy source of the future. Currently, more than 90% of world hydrogen production is made via catalytic steam methane reforming (SMR). A performing catalyst favors thermodynamic equilibrium that ensures good hydrogen selectivity. This research explores the potential of SMR yield intensification using experimental micro reactor and active noble metal catalyst (Rhodium aluminide and Ruthenium aluminide). For that purpose, a laboratory scale SMR test rig bench was designed, fabricated and developed. A new micro channel reactor with interchangeable catalyst modules for methane conversion process was set up and tested. The rig is able to provide evaluation of SMR experimental tests, such as catalyst performance, conversion rate and products at output stream, with controlled reactants steam to carbon ratio up to 5:1 and reaction temperature up to 700°C. The developed conventional and noble metal catalyst for this research, affirmed and proved that the combination of test rig bench and micro reactor managed to generate methane conversion according to the theory related to material catalyst. From this work, reaction temperature 650°C and steam to carbon ratio of 3:1 were found to yield the optimum methane conversion and hydrogen formation for the developed catalyst. Using such setup, the use of noble metal catalyst was able to reform methane to hydrogen within 1 minute from the start of reaction as compared to 60 minutes using conventional catalyst. It was found that the rate of reaction (methane disappearing rate) of $-r'_{CH_4}$ (mol CH_4 / g catalyst.s), for Rhodium aluminide yield the highest of 181.58, followed by Ruthenium aluminide with 154.39 and lastly Nickel aluminide of 1.32. The outcomes of this work has the potential to be scaled up for hydrogen production supply chain system of future fuel-cell electric vehicle transportation sector especially in any region with affordable natural gas price.

ABSTRAK

Peningkatan terhadap penggunaan sumber tenaga dunia telah mewujudkan keinginan untuk mencari sumber tenaga baharu sebagai langkah untuk menangani fenomena tersebut. Tenaga dari sumber hidrogen dipercayai menjadi calon utama tenaga masa hadapan. Lebih 90% penghasilan hidrogen ialah melalui proses tindak balas kimia *Steam Methane Reforming* (SMR). Sesebuah pemangkin membantu fasa keseimbangan termodinamik bagi SMR dan meningkatkan pengeluaran hidrogen. Kajian ini meneroka kebolehpayaan peningkatan hasil SMR dengan menggunakan reaktor skala mikro dan pemangkin *noble metal* (*Rhodium aluminide* dan *Ruthenium aluminide*). Oleh itu, sebuah pelantar ujian proses SMR berskala makmal telah direka, dibina dan dibangunkan. Reaktor pada skala mikro dibina dan diuji dengan mempunyai ciri kebolehpayaan menggunakan pelbagai jenis pemangkin. Pelantar ujian tersebut, menghasilkan data SMR seperti prestasi pemangkin, penukaran bahan tindak balas, produk terhasil dan dikawal pada nisbah mol bahan tindak balas sehingga 5:1 dan suhu tindak balas sehingga 700°C. Pemangkin dalam kajian ini, telah menunjukkan kesetaraan menurut teori asas SMR tatkala menggunakan pelantar ujian proses SMR dan reaktor skala mikro. Hasil kajian ini menunjukkan bahawa suhu tindak balas 650°C dan nisbah mol bahan tindak balas 3:1 menghasilkan penukaran metana dan pembentukan hidrogen yang optimum. Berdasarkan tetapan berkenaan, penggunaan *noble metal* telah menunjukkan masa tindak balas penukaran metana kepada hidrogen seawal 1 minit pertama, berbanding pemangkin konvensional pada 60 minit yang pertama. Kadar tindak balas penukaran metana bagi setiap berat pemangkin dan masa, *Rhodium aluminide* telah menunjukkan nilai tertinggi iaini 181.58, diikuti *Ruthenium aluminide* dengan nilai 154.39 dan *Nickel aluminide* pada nilai 1.32. Hasil kajian berupaya menjadi platform fasa peningkatan kepada skala besar penghasilan hidrogen dimasa hadapan, terutama di dalam sektor pengangkutan khususnya bagi sistem rangkaian pembekalan untuk kenderaan *fuel-cell* di kawasan yang mempunyai sumber gas semulajadi pada kadar harga mampu milik.

CONTENTS	vii
LIST OF TABLES	xii
LIST OF FIGURES	xiv
LIST OF SYMBOLS AND ABBREVIATIONS	xvii
LIST OF APPENDICES	xx
CHAPTER 1 INTRODUCTION	1
1.1 Research Background	1
1.2 Problem statement	5

TITLE	i
DECLARATION	ii
DEDICATION	iii
ACKNOWLEDGEMENT	iv
ABSTRACT	v
ABSTRAK	vi
CONTENTS	vii
LIST OF TABLES	xii
LIST OF FIGURES	xiv
LIST OF SYMBOLS AND ABBREVIATIONS	xvii
LIST OF APPENDICES	xx
CHAPTER 1 INTRODUCTION	1
1.1 Research Background	1
1.2 Problem statement	5
1.3 Objectives	8
1.4 Scopes of study	9
1.5 Overall Project Layout	10
1.6 Expected outcomes	13
1.7 Thesis Outline	14
CHAPTER 2 LITERATURE REVIEW	15
2.0 Introduction	15
2.1 Hydrogen as a Renewable Energy	15
2.1.1 Optimization of Future Hydrogen Energy in Transportation Sector	16
2.2 Reformer Technologies	17
2.2.1 Steam Methane Reforming	21

2.2.2	Novel Reformer of SMR	24
2.3	Micro Channel Reactor in Steam Methane Reforming (SMR)	27
2.3.1	Physical Properties of Micro Channel Reactor	30
2.3.2	Type of Micro Channel	32
2.3.3	Microstructure: Scale Up to Commercial Capacity	34
2.4	Catalyst in Steam Methane Reforming	35
2.4.1	Nickel Catalyst	36
2.4.2	Noble Metal Catalyst	38
2.4.3	Catalyst Deposition	40
2.4.4	Rate of Reaction	41
2.4.5	Catalyst in Micro Channel Reactor	42
2.5	Conversion Platform	43
2.5.1	Route of Process System	45
2.5.2	Process Overview	46
2.5.3	Micro plant Design Basis	47
2.5.4	Development of Conceptual Design	49
2.5.4.1	Conceptual Design Level 1-Process Selection Overview	50
2.5.4.2	Conceptual Design Level 2 - Chemical Synthesis	51
2.5.4.3	Conceptual Design Level 3 - Recycle Stream	52
2.5.4.4	Conceptual Design Level 4 - Chemical Separation	52
2.6	Gap Analysis Work Studies	53
CHAPTER 3 METHODOLOGY		57
3.1	Introduction	57
3.2	Methodology Chart	58
3.3	Conceptual Design of Mobile Steam Methane Reforming's Test Rig	59
3.3.1	Development of Process Flow Diagram (PFD) and Process & Instrumentation Diagram (P&ID)	59
3.3.2	P&ID Pretreatment Stage	61

3.3.3	P&ID Upstream Stage	65
3.3.4	P&ID Downstream Stage	65
3.4	Design and Fabrication of Unit Operation	67
3.4.1	Steam Generator	69
3.4.2	Condenser	71
3.4.3	Separator – Liquid & Gas Recovery	73
3.4.4	Dryer – Vapor Recovery	74
3.4.5	Flare – Reformat Purifier	76
3.5	Conceptual Design of Micro reactor system	77
3.5.1	Superheated Steam Converter Coils	78
3.5.2	Micro Channel Reactor Module	78
3.5.3	Cold Commissioning of Micro reactor system	79
3.6	SMR Test Rig Bench and Micro Reactor System Function Test	82
3.7	Catalytic Behavior Analysis	83
3.7.1	Catalyst Precursor	83
3.7.2	Catalyst Activation	83
3.7.3	Catalyst Test Analysis	84
3.7.3.1	SMR Yields Characterization	88
3.7.3.2	Methane Conversion and Mole Balance Equation for Flow Reactors	92
3.7.3.3	Design of Rate of Reaction (Methane disappearing rate)	94

CHAPTER 4 RESULTS AND DISCUSSION 96

4.0	Introduction	96
4.1	Development of SMR Test Rig Bench	96
4.1.1	Steam Methane Reforming Test Rig Bench Function Test	97
4.1.2	Standard Operating Procedure of Steam Methane Reforming Test Rig	102
4.1.2.1	General Safety	103
4.1.2.2	Operator Safety	103
4.1.2.3	Emergency Response	104
4.1.2.4	Process Safety	104

4.1.2.5	Communication	105
4.1.2.6	Recommended Operating Procedure	105
4.1.2.7	Materials and Equipment	106
4.1.2.8	Box Furnace Routine Check	106
4.1.2.9	Start-up Procedure	106
4.1.2.10	Pretreatment Stage - Saturated Steam Generator	107
4.1.2.11	Pretreatment Stage - Superheated Steam Converter	108
4.1.2.12	Upstream Stage– Micro channel reactor	108
4.1.2.13	Steam to Carbon Ratio Analysis	109
4.1.2.14	Downstream Stage	110
4.1.2.15	Catalyst Activation Stage	112
4.1.2.16	Shutdown Procedure	112
4.2	The Art of Micro Reactor Systems	113
4.2.1	Micro Reactor Systems	113
4.2.2	Micro Reactor Cold Commissioning	117
4.2.2.1	Vacuum Test	117
4.2.2.2	Hydrostatic Pressure Test	118
4.2.2.3	Static Pressure Test	119
4.2.2.4	Steam to Carbon ratio	119
4.3	Reforming Catalytic Analysis	120
4.3.1	Catalytic Behavior Effect on Steam Methaner Reforming Yields	120
4.3.2	Effect of Reaction Temperature on SMR	121
4.3.3	Effect of Steam to Carbon Ratio on Steam Methane Reforming Yields	126
4.3.4	Effect of Multiple Type Catalyst Loading on SMR	131
4.4	Summary of Findings	137
4.4.1	Mobile Steam Methane Reforming Test Rig	137
4.4.2	Micro Channel Reactor	138
4.4.3	Catalytic Behavior Effect on SMR Yield	139

CHAPTER 5 CONCLUSIONS AND RECOMMENDATIONS	141
5.1 Conclusions	141
5.2 Recommendations	142
REFERENCES	144
APPENDIX A : LIST OF PUBLISHED PAPERS DURING STUDY	156
APPENDIX B : LIST OF AWARD AND PATENT RELATED TO THIS STUDY	157
APPENDIX C : PROCESS & INSTRUMENTATION DIAGRAM	158
APPENDIX D : CONCEPTUAL DESIGN OF STEAM METHANE REFORMING TEST RIG	159
APPENDIX E : MICRO CHANNEL REACTOR	165
APPENDIX F : SMR DATA SHEET	173
APPENDIX G : GC ANALYSIS RESULTS	177
APPENDIX H : Dräger MSI EM200 ANALYSIS ON CARBON MONOXIDE CONVERSION	179
APPENDIX I : SMR YIELD	181
VITA	187

LIST OF TABLES

TABLE	TITLE	PAGE
1.1	Interaction relation for driving factor of novel interchangeable catalyst reformer	12
2.1	Comparison of syngas generation technology (Gangadharan et al., 2012; Holladay et al., 2009; Samuel, 2003)	19
2.2	Relative activities for SMR at operating condition of 550°C, S/C: 4, and 1 bar (Beurden, 2004)	40
2.3	Comparison of related work done by previous researcher	55
3.1	The saturated steam generator physical properties	70
3.2	Physical properties of condenser system	72
3.3	Liquid-gas separating system	74
3.4	Dryer system physical properties	75
3.5	Flare system physical properties	76
3.6	Hot commissioning parameter	82
3.7	Catalyst activation parameter	84
3.8	Catalyst test parameter	87
3.9	“In house” configuration based on ASTM D1945	90
4.1	SMR test bench hot commissioning	100
4.2	Steam to carbon ratio	110
4.3	SMR Data sheet	111

4.4	Micro reactor system physical properties	114
4.5	Vacuum test	117
4.6	Hydrostatic pressure test for load and without load plate condition	118
4.7	Static pressure test	119
4.8	Comparison works between previous researcher and current analysis	137



LIST OF FIGURES

FIGURE	TITLE	PAGE
1.1	Fossil fuel projection of production and demand (Daud, 2006)	2
1.2	Hydrogen road map for Malaysia (Daud, 2006)	3
1.3	Fuel processing of gaseous, liquid, and solid fuels for hydrogen production (Holladay et al., 2009)	5
1.4	Interaction relationship diagram of novel interchangeable catalyst reformer	11
2.1	Micro channel reactor structure: Top (at the left) and cross- sectional (at the right) views of the microchannel configuration (1): engineered metal housing; (2): open microchannels; (3): coated catalyst layers; (4): substrate plate; (5): ceramic wool plug (Simsek et al., 2011)	28
2.2	Pathway of reactant flow inside micro channel (IP2017300009, 2017; Simsek et al., 2011)	29
2.3	Micro channel reactor : (a) Multi coil type (Izquierdo et al., 2012), (b) Radial pin hole type (Z. Liu et al., 2012)	29
2.4	The architectural structure of micro channel (Morris, 2016)	31
2.5	Coil based (Morris, 2016)	32
2.6	Pinhole based (Morris, 2016)	33
2.7	Radial based (Morris, 2016)	33
2.8	Physical interpretation of Langmuir-Hinshelwood model (Hou & Hughes, 2001)	42
2.9	General steam methane reforming (SMR) process flow diagram (PFD) (Madon et al., 2015)	44
2.10	SMR Process overview (Seris E.L.C, 2006)	47
2.11	Conceptual design flow analysis of a chemical process	50

2.12	Input-output of Steam Methane Reforming process	51
2.13	Gap analysis works	56
3.1	Methodology Flow Chart	58
3.2	Process flow diagram of steam methane reforming test bench	50
3.3	Overall view of process and instrumentation diagram of SMR test rig bench	62
3.4	Process and instrumentation diagram of pretreatment stage	64
3.5	Process and instrumentation diagram of upstream stage	65
3.6	Process and instrumentation diagram of downstream stage	67
3.7	Basic flow diagram of hydrogen production	67
3.8	Flow analysis of unit operation involves in steam methane reforming process.	68
3.9	Saturated steam generator unit	70
3.10	Illustration of condenser	73
3.11	Illustration of separator	74
3.12	Illustration of dryer	75
3.13	Illustration of flare system	76
3.14	Schematic diagram of vacuum test	80
3.15	Schematic diagram of hydrostatic pressure test	81
3.16	Schematic diagram of static pressure test	82
3.17	Ellingham diagram for catalyst activation	85
3.18	Flow diagram of characterization for SMR yield	89
3.19	Tedlar Sampling Bag 1L	90
3.20	a) Inject sample out of Tedlar bag, b) Inject sample into GC	91
3.21	Dräger MSI EM200	92
4.1	a) Completed chasis test rig, b) Isometric view schematic diagram of assemble SMR test rig bench (continued)	98
4.1	c) Left view schematic diagram of assemble SMR test rig bench, d) Right view schematic diagram of assemble SMR test rig bench	99
4.2	Process flow of assembling test rig	100
4.3	Photo of complete mobile SMR test rig bench	101
4.4	An exploded isometric view of micro reactor system	115
4.5	Installation of coated substrate plate inside micro reactor	

	system	116
4.6	Photo of complete micro reactor system	117
4.7	Methane flow rate based on steam to carbon ratio	120
4.8	Effect of reaction temperature on methane conversion (error bars of 95% confident interval mean value statistic)	122
4.9	Effect of reaction temperature on SMR yield	125
4.10	Effect of reaction temperature on methane disappearing rate	126
4.11	Steam to carbon ratio effect on methane conversion (error bars of 95% confident interval mean value statistic)	128
4.12	Summary effect steam to carbon ratio on SMR yield	130
4.13	Effect of reaction steam to carbon ratio on methane disappearing rate	131
4.14	Multiple type of catalyst effect on methane conversion (error bars of 95% confident interval mean value statistic)	132
4.15	Multiple catalyst loading effect on SMR yield	134
4.16	Effect of multiple type catalyst on methane disappearing rate	136



LIST OF SYMBOLS AND ABBREVIATIONS

Al	Aluminum
AIGA	Asian Industrial Gas Association
Al ₂ O ₃	Alumina oxide
C	Char
CH ₄	Methane
CO	Carbon monoxide
CoGe	Cobalt Germanium
CO ₂	Carbon dioxide
C-101	Condenser (101 = referring number of unit)
D-101	Dryer (101 = referring number of unit)
DME	Dimethyl ester
dV	Differential of reactor volume
dW	Differential of embedded catalyst weight inside reactor
dX	Differential of reaction conversion
Eqn.	Equation
F _{CH₄} ^o	Molar flow rate of methane in feed
F _{CH₄}	Molar flow rate of methane at output
FIC 101	Flow Indicator Controller (101 = referring number of unit)
FT	Fischer Tropsch
F-101	Furnace (101 = referring number of unit)
H ₂	Hydrogen
H-101	Steam generator (101 = referring number of unit)
ICE	Internal combustion engine
Ir	Iridium
kg	kilogram
lph	liter per hour
lpm	liter per minute

Mb/d	Million barrel per day
min	minute
ml	milliliter
MW	molecular weight
m ³	meter cube
NaOH	Sodium hydroxide
Na ₂ CO ₃	Sodium carbonate
Ni	Nickel
NiO	Nickel oxide
Ni ₃ Al	Nickel aluminide
Ni ₃ Sn	Nisnite mineral
Ni/Al ₂ O ₃	Nickel support alumina oxide
Pd	Palladium
PEM	Proton exchange membrane
PFD	Process Flow Diagram
PI 101	Pressure indicator (101 = referring number of unit)
PSA	Pressure swing absorber
PtGe	Platinum Germanium
PV	Process value
Pt	Platinum
P&ID	Process & Instrumentation Diagram
RBDO	Refined Bleach Deodorized Palm Oil
Rh	Rhodium
Ru	Ruthenium
R-101	Reformer (101 = referring number of unit)
s	seconds
SOP	Standard Operating Procedure
SMR	Steam methane reforming
S-101	Separator (101 = referring number of unit)
SSC-101	Superheated steam converter (101 = referring number of unit)
SS304	stainless steel grade of 304
SS316	stainless steel grade of 316
TI 101	Temperature indicator (101 = referring number of unit)
V-101	Ball valve (101 = referring number of unit)

W	weight % catalyst
WGS	Water gas shift
WHSV	Weight hourly space velocity
X_{CH_4}	Methane conversion
Å	Angstrom measurement
°C	degree Celsius
ΔH	Enthalpies
wt%	weight percent
2θ	Bragg reflection
μl	Micro liter
ξ_1	Extent reaction for SMR equation
ξ_2	Extent reaction for WGS equation
(\dot{m})	Steam mass flow rate
\dot{n}_i	Mole flow rate of species exit the reactor
$\dot{n}_{o,i}$	Mole flow rate of species into the reactor
$-\dot{r}_{CH_4}$	Rate of reaction (mol CH_4 /g catalyst.s)
$-\dot{r}_{CH_4}$	Rate of reaction (mol CH_4 / $dm^3.s$)



PT TAAUTHM
PERPUSTAKAAN TUNKU TUN AMINAH

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
C.1	Full schematic diagram of SMR Test Rig Bench P&ID	158
D.1	Schematic drawing SMR Test Rig CH001	159
D.2	Schematic drawing SMR Test Rig CH002	159
D.3	Schematic drawing SMR Test Rig CH003	160
D.4	Schematic drawing distilled water tank	160
D.5	Schematic diagram of steam generator BOIL 001	161
D.6	Schematic diagram of steam generator BOIL 002	161
D.7	Schematic diagram of steam generator BOIL 003	162
D.8	Schematic diagram of condenser COND 001	162
D.9	Schematic diagram of condenser COND 002	163
D.10	Schematic diagram of separator	163
D.11	Schematic diagram of condenser dryer	164
D.12	Schematic diagram of flare tower	164
E.1	Schematic diagram of micro reactor version 1 MRV1 001	165
E.2	Schematic diagram of micro reactor version 1 MRV1 002	165
E.3	Schematic diagram of micro reactor version 1 MRV1 003	166
E.4	Schematic diagram of micro reactor version 2 & 3 MRV2 001	166
E.5	Schematic diagram of micro reactor version 2 & 3 MRV2 002	167
E.6	Schematic diagram of micro reactor version 2 & 3 MRV2 003	167
E.7	Schematic diagram of micro reactor version 2 & 3 MRV2 004	167
E.8	Schematic diagram of micro reactor version 2 & 3 MRV2 005	167
E.9	Schematic diagram of micro reactor version 4 MRV2 001	169
E.10	Schematic diagram of micro reactor version 4 MRV2 002	169
E.11	Schematic diagram of micro reactor version 4 MRV2 003	170
E.12	Schematic diagram of micro reactor version 4 MRV2 004	170
E.13	Schematic diagram of micro reactor version 4 MRV2 005	171
E.14	Vacuum test apparatus	171

E.15	Hydrostatic pressure test setup	172
E.16	Static pressure test	172
F.1	SMR data sheet (500°C / S:C 3)	173
F.2	SMR data sheet (550°C / S:C 3)	173
F.3	SMR data sheet (600°C / S:C 3)	173
F.4	SMR data sheet (650°C / S:C 3)	174
F.5	SMR data sheet (700°C / S:C 3)	174
F.6	SMR data sheet (S:C 2/650°C)	174
F.7	SMR data sheet (S:C 3/650°C)	175
F.8	SMR data sheet (S:C 4/650°C)	175
F.9	SMR data sheet (Nickel aluminide / 650°C/S:C 3)	175
F.10	SMR data sheet (Ruthenium aluminide / 650°C/S:C 3)	176
F.11	SMR data sheet (Rhodium aluminide / 650°C/S:C 3)	176
G.1	GC analysis of reaction temperature effect on methane conversion	177
G.2	GC analysis of steam to carbon ratio effect on methane conversion	177
G.3	GC analysis of multiple type of catalyst loading effect on methane conversion	178
H.1	Analysis of reaction temperature effect on carbon monoxide conversion	179
H.2	Analysis of steam to carbon ratio effect on carbon monoxide conversion	179
H.3	Analysis of multiple type of catalyst loading effect on carbon monoxide conversion	180
I.1	Analysis of reaction temperature effect on SMR yield	182
I.2	Analysis of steam to carbon ratio effect on SMR yield	183
I.3	Analysis of multiple type of catalyst effect on SMR yield	185
I.4	Analysis of reaction temperature effect on methane disappearing rate	185
I.5	Analysis of steam to carbon ratio effect on methane disappearing rate	186
I.6	Analysis of multiple type of catalyst effect on methane disappearing rate	186

CHAPTER 1

INTRODUCTION

1.1 Research Background

It is reported the distribution of proved fossil fuel reserves from 1996 to 2016 had showed that the global oil demand grew by 1.6 million barrels per day and the oil reserves also increased at 1706.7 thousand million barrels in 2016, in consequences of both demand and supply trending (British Petroleum, 2017). It is believed that possibility of demand shortage will occur since fossil fuel is non-renewable. In addition to the cost and demand of fossil fuel energy, there was a significant environmental concern regarding petroleum fuel based usage. The recent analysis estimated that pollutants may be high enough to bear on public health and the environment in areas where 50% of develop country exist. Report by Daud, (2006) and Kamarudin et al., (2009) air pollution by transportation and industrial sectors are principally due to the using of fossil oil and natural gas as their source of fuel. Figure 1.1 shows the projection of production and demand of fossil fuel generally at world level and specifically at Malaysia level. Apparently, extreme depending on the fossil fuel lead to shortage of fuel energy sources and high potential of pollutant as the emission from combustion of the fossil fuel. Thus, in order to deal with these issues, there has been an effort to diversify energy supply for better energy efficiency and cleaner fuels. The utilization of renewable energy, capable to encounter the energy demand and to reduce the growth rate of greenhouse gases (GHG), which mainly concentrate of Carbon Dioxide (CO₂) as the emission from the fossil fuel usage. In Malaysia, renewable energy development is mainly focused on biomass-based power generation (BIOGEN), solar and hydrogen energy. It's believed that, the GHG impact from industrial sector and transportation should be reduced by 3.8% within 5 years

(Daud, 2006, Holladay, et al., 2009; Kamarudin et al., 2009). The hydrogen energy at a smaller extent identified as most viable long term renewable energy as alternative fuel compared to the fossil fuel.




Figure 1.1 : Fossil fuel projection of production and demand (Daud, 2006).

It is widely accepted that hydrogen energy was among the clean, efficient and pollution free energy source in the future. The hydrogen energy becomes the main energy sources as fuel in fuel-cell system especially for the transportation sector. Besides that, this hydrogen is widely utilized as feedstock for food processing, chemical production and refining industries. Reported by Daud, (2006), Kamarudin et al., (2009) and Khan et al., (2010) the demand for hydrogen is expected to rapidly increase due its potential as major energy sources in the future. Figure 1.2 describes the route map of hydrogen energy, specifically in Malaysia which had been exhibited at International Seminar on The Hydrogen Economy for Sustainable Development, Reykjavik Iceland (Daud, 2006). The R&D of the hydrogen production and storage technologies has been started as early as 2002. This road map has become the baseline for hydrogen research area in Malaysia. This road map is mainly focused on transportation sector whereby the Hydrogen is used as energy sources for zero carbon emission fuel (Kamarudin et. al., 2009).





Figure 1.2: Hydrogen road map for Malaysia (Daud, 2006).

Established along the theory of stoichiometry equation for combustion reaction, Eqn. 1.1 shows any hydrocarbon produces carbon dioxide. The concentrated carbon dioxide leads to the greenhouse gas phenomenon and becomes worst polluted to the environment. Eqn 1.2 shows the combustion of hydrogen, which primarily produces water vapor. The equation demonstrate that the hydrogen is clean and zero carbon pollutant fuel (Sciazko et al., 2014; Udengaard et al., 2004; Verykios & Piga, 2000).



Reported by Holladay et. al., (2009) highlighted that the most developed and most used technology in hydrogen production was reforming of the hydrocarbon fuels, due its advantage such as highly efficient, low cost and already achieve commercial and long term stage in industry compare to non-reforming (biomass gasification, photolysis, electrolysis and etc). Furthermore, presently almost 96% of the world's hydrogen demand, including in Malaysia, is provided by traditional fossil fuels, and about half of it, comes from natural gas; which the main composition is methane (Bartels et. al., 2010; Bej et. al., 2013; Florin & Harris, 2007; Kamarudin et al., 2009; Udengaard, 2004). The production of hydrogen from various hydrocarbons, especially methane mainly comes from the chemical reaction process of catalytic reforming technologies which consist such as steam methane reforming, partial oxidation, and auto thermal reforming. Among these, catalytic steam methane reforming has the advantage of relatively low reaction temperature and high hydrogen content in the reforming products, and it is currently considered as the most cost efficient and highly evolved case of reforming for hydrogen production. Whereby, since the early 1950s, a considerable efforts have been set into the investigations of steam methane reforming (SMR) and its kinetics (Kamarudin et al., 2009; Khan et al., 2010; Wang et al., 2012; Wang et al., 2013).

The SMR is a strongly endothermic reaction inside tubular reactor with Nickel based catalyst, which requires external heating of the reactor tubes. This process is carried out by either the direct firing (as in radiant reformers) or by heat exchange with

REFERENCES

- Aaltonen, T., Ritala, M., & Leskelä, M. (2005). ALD of Rhodium Thin Films from Rh(acac)[sub 3] and Oxygen. *Electrochemical and Solid-State Letters*, 8(8), C99.
- Abeden, Z. bin Z. (2016). Eksperimen Untuk Kolum Hidrokarbon C1-C5 Bagi Analisis Gas Kromatografi. *Universiti Tun Hussein Onn Malaysia. Undergraduates Thesis*.
- Aloisi, I., Giuliano, A. Di, Carlo, A. Di, Foscolo, P. U., Courson, C., & Gallucci, K. (2017). Sorption enhanced catalytic Steam Methane Reforming : Experimental data and simulations describing the behaviour of bi-functional particles. *Journal of Chemical Engineering*. 314, 570–582.
- Anwar Ul-Hamid, Abdul Quddusa, Huseyin Saricimen, & Hatim Dafalla. (2015). Corrosion Behavior of Coarse- and Fine-Grain Ni Coatings Incorporating NaH₂PO₄.H₂O Inhibitor Treated Substrates. *Materials Research*, 18(1), 20–26.
- Armor, J. N. (1999). The multiple roles for catalysis in the production of H₂. *Applied Catalysis A: General*, 176(2), 159–176.
- Barelli, L., Bidini, G., Gallorini, F., & Servili, S. (2008). Hydrogen production through sorption-enhanced steam methane reforming and membrane technology: A review. *Energy*, 33(4), 554–570.
- Bartels, J. R., Pate, M. B., & Olson, N. K. (2010). An economic survey of hydrogen production from conventional and alternative energy sources. *International Journal of Hydrogen Energy*, 35(16), 8371–8384.
- Bej, B., Pradhan, N. C., & Neogi, S. (2013). Production of hydrogen by steam reforming of methane over alumina supported nano-NiO/SiO₂ catalyst. *Catalysis Today*, 207, 28–35.
- Beurden, P. Van. (2004). *On the catalytic aspects of steam methane reforming : A Literature Survey*. Energy Centre Netherland (Vol. 04).
- British Petroleum. (2017). *BP Statistical Review of World Energy 2017*. British Petroleum. London. economics/statistical-review-2017/bp-statistical-review-of-
- Butcher, H., Quenzel, C. J. E., Breziner, L., Mettes, J., Wilhite, B. a., & Bossard, P.

- (2014). Design of an annular microchannel reactor (AMR) for hydrogen and/or syngas production via methane steam reforming. *International Journal of Hydrogen Energy*, 1–12.
- C.M. Ward-Close, R.Minor, P. J. D. (1996). Intermetallic-matrix composites-a Review. *Intermetallics* 4, 9795(95), 217–229.
- Cao, C., Zhang, N., Chen, X., & Cheng, Y. (2015). A comparative study of Rh and Ni coated microchannel reactor for steam methane reforming using CFD with detailed chemistry. *Chemical Engineering Science*, 137, 276–286.
- Cao, C., Zhang, N., & Cheng, Y. (2016). Numerical analysis on steam methane reforming in a plate microchannel reactor: Effect of washcoat properties. *International Journal of Hydrogen Energy*, 41(42), 18921–18941.
- Charisiou, N. D., Siakavelas, G., Papageridis, K. N., Baklavaridis, A., Tzounis, L., Avraam, D. G., & Goula, M. A. (2016). Syngas production via the biogas dry reforming reaction over nickel supported on modified with CeO₂ and / or La₂O₃ alumina catalysts, 31, 164–183.
- Chen, J., Yan, L., Song, W., & Xu, D. (2016). Operating strategies for thermally coupled combustion-decomposition catalytic microreactors for hydrogen production. *International Journal of Hydrogen Energy*, 41(46), 21532–21547.
- Cheng, Y., Zhai, X., Cheng, Y., Zhang, Z., & Jin, Y. (2011). Steam reforming of methane over Ni catalyst in micro-channel reactor. *International Journal of Hydrogen Energy*, 36, 7105–7113.
- Chibane, L., & Djellouli, B. (2011). Methane Steam Reforming Reaction Behaviour in a Packed Bed Membrane Reactor. *International Journal of Chemical Engineering and Applications*, 2(3), 147–156.
- Cohron, J. W., George, E. P., Heatherly, L., Liu, C. T., & Zeeb, R. H. (1996). Effect of low-pressure hydrogen on the room-temperature tensile ductility and fracture behavior of N & Al, 9795(96), 497–502.
- Czernik, S., Evans, R., & French, R. (2007). Hydrogen from biomass-production by steam reforming of biomass pyrolysis oil☆. *Catalysis Today*, 129, 265–268.
- Czernik, S., French, R., Feik, C., & Chornet, E. (2002). Production of hydrogen from biomass by pyrolysis steam reforming. *Advances in Hydrogen Energy*, 87–91.
- Daud, W. R. W. (2006). Hydrogen Economy:Perspective From Malaysia. In W. R. W. Daud (Ed.), *International Seminar on the Hydrogen Economy for Sustainable Development* (p. 30). Reykjavik, Iceland.

- de Smet, C. R. H., de Croon, M. H. J. M., Berger, R. J., Marin, G. B., & Schouten, J. C. (2001). Design of adiabatic fixed-bed reactors for the partial oxidation of methane to synthesis gas. Application to production of methanol and hydrogen-for-fuel-cells. *Chemical Engineering Science*, 56, 4849–4861.
- Delparish, A., & Avci, A. K. (2016). Intensified catalytic reactors for Fischer-Tropsch synthesis and for reforming of renewable fuels to hydrogen and synthesis gas. *Fuel Processing Technology*, 151, 72–100.
- Deutschmann, O., Maier, L. ., Riedel, U., Stroemman, A. ., & Dibble, R. . (2000). Hydrogen assisted catalytic combustion of methane on platinum. *Catalysis Today*, 59(1), 141–150.
- Doma, M. M.-, Jó, P., Jankiewicz, B. J., & Bartosewicz, B. (2016). Study of cyclic Ni₃Al catalyst pretreatment process for uniform carbon nanotubes formation and improved hydrogen yield in methanol decomposition, 171–177.
- Douglas, J. M. (1988). Conceptual Design of Chemical Processes. (B. J. C. and J. W. Bradley, Ed.) (1st Editio). Singapore: McGraw Hill Book Company.
- Dupont, V., Ross, A. B., Knight, E., Hanley, I., & Twigg, M. V. (2008). Production of hydrogen by unmixed steam reforming of methane, 63, 2966–2979.
- Dybkjær, I., Ovesen, C. V., Schjødt, N. C., Sehested, J., & Thomsen, S. G. (2011). Journal of Natural Gas Science and Engineering Natural gas to synthesis gas e Catalysts and catalytic processes, 3.
- Eduardo, L., Oliveira, G., & Carlos, A. (2009). Steam Methane Reforming in a Ni/Al₂O₃ Catalyst: Kinetic and Diffusional Limitations in Extrudates. *The Canadian Journal of Chemical Engineering*, 87(6), 945–956.
- Eswaramoorthi, I., & Dalai, A. K. (2009). A comparative study on the performance of mesoporous SBA-15 supported Pd-Zn catalysts in partial oxidation and steam reforming of methanol for hydrogen production. *International Journal of Hydrogen Energy*, 34(6), 2580–2590.
- Fabas, A., Put, A. R., Doublet, S., Domergue, D., Salem, M., & Monceau, D. (2017). Metal dusting corrosion of austenitic alloys at low and high pressure with the effects of Cr, Al, Nb and Cu, 123(September 2016), 310–318.
- Florin, N. H., & Harris, A. T. (2007). Hydrogen production from biomass coupled with carbon dioxide capture: The implications of thermodynamic equilibrium. *International Journal of Hydrogen Energy*, 32, 4119–4134.
- Gangadharan, P., Kanchi, K. C., & Lou, H. H. (2012). Evaluation of the economic and

- environmental impact of combining dry reforming with steam reforming of methane. *Chemical Engineering Research and Design*, 90(March), 1956–1968.
- Ghorbanzadeh, A. M., Lotfalipour, R., & Rezaei, S. (2009). Carbon dioxide reforming of methane at near room temperature in low energy pulsed plasma. *International Journal of Hydrogen Energy*, 34(1), 293–298.
- Graf, P. O., Mojet, B. L., van Ommen, J. G., & Lefferts, L. (2007). Comparative study of steam reforming of methane, ethane and ethylene on Pt, Rh and Pd supported on yttrium-stabilized zirconia. *Applied Catalysis A: General*, 332, 310–317.
- Group, T. F. (2013). World Hydrogen Market. *Freedonia*, 331 pages. Retrieved from <http://www.reportlinker.com/p0944103-summary/World-Hydrogen-Industry.html>
- Halabi, M. H., De Croon, M. H. J. M., Van Der Schaaf, J., Cobden, P. D., & Schouten, J. C. (2010). Low temperature catalytic methane steam reforming over ceria-zirconia supported rhodium. *Applied Catalysis A: General*, 389, 68–79.
- Haynes, B. S., & Johnston, A. M. (2011). Process design and performance of a microstructured convective steam – methane reformer, 178, 34–41.
- Hoang, D. L., Chan, S. H., & Ding, O. L. (2005). Methane in an Oxygen Permeable. *ICHeme Journal*, (83(A2)), 177–186.
- Holladay, J. D., Hu, J., King, D. L., & Wang, Y. (2009). An overview of hydrogen production technologies. *Catalysis Today*, 139, 244–260.
- Hou, K., & Hughes, R. (2001). The kinetics of methane steam reforming over a Ni/ α -Al₂O₃ catalyst. *Chemical Engineering Journal*, 82(1–3), 311–328.
- Hwang, S. M., Kwon, O. J., & Kim, J. J. (2007). Method of catalyst coating in micro-reactors for methanol steam reforming. *Applied Catalysis A: General*, 316(1), 83–89.
- Inayat, A., Ahmad, M. M., Mutalib, M. I. A., & Yusup, S. (2012). Process modeling for parametric study on oil palm empty fruit bunch steam gasification for hydrogen production. *Fuel Processing Technology*, 93(1), 26–34.
- Izquierdo, U., Barrio, V. L., Cambra, J. F., Requies, J., Güemez, M. B., Arias, P. L., ... Arraibi, J. R. (2012). Hydrogen production from methane and natural gas steam reforming in conventional and microreactor reaction systems. *International Journal of Hydrogen Energy*, 37, 7026–7033.
- Jeon, Y., Kim, H., Lee, C., Lee, S., Song, S., & Shul, Y. gun. (2017). Efficient methane reforming at proper reaction environment for the highly active and stable fibrous

- perovskite catalyst. *Fuel*, 207, 493–502.
- Jianguo Xu, Froment, G. F. (1989). Methane Steam Reforming , Methanation and Water-Gas Shift : I . Intrinsic Kinetics. *AIChE Journal*, 35(1), 88–96.
- Jin, M. H., Lee, C. B., Lee, D. W., Lee, S. W., Park, J. W., Oh, D., Park, J. S. (2016). Microchannel methane steam reformers with improved heat transfer efficiency and their long-term stability. *Fuel*, 176, 86–92.
- Kamarudin, S. K., Daud, W. R. W., Yaakub, Z., Misron, Z., Anuar, W., & Yusuf, N. N. a N. (2009). Synthesis and optimization of future hydrogen energy infrastructure planning in Peninsular Malaysia. *International Journal of Hydrogen Energy*, 34(5), 2077–2088.
- Karagiannidis, S., Mantzaras, J., & Boulouchos, K. (2011). Stability of heterogeneous/homogeneous combustion in propane- and methane-fueled catalytic microreactors: Channel confinement and molecular transport effects. *Proceedings of the Combustion Institute*, 33(2), 3241–3249.
- Karim, A., Bravo, J., Gorm, D., Conant, T., & Datye, A. (2005). Comparison of wall-coated and packed-bed reactors for steam reforming of methanol. *Catalysis Today*, 110(1–2), 86–91.
- Khan, Z., Yusup, S., Ahmad, M. M., Chok, V. S., Uemura, Y., & Sabil, K. M. (2010). Review on hydrogen production technologies in Malaysia. *International Journal of Engineering*, 10(02), 111–118.
- Kim, H. Y., Chung, D. S., & Hong, S. H. (2005). Reaction synthesis and microstructures of NiAl / Ni micro-laminated composites, 396, 376–384.
- Kolb, G., & Hessel, V. (2004). Micro-structured reactors for gas phase reactions. *Chemical Engineering Journal*, 98(1–2), 1–38.
- Kook, S., Keun, S., Ok, J., Seong, J., & Chul, Y. (2013). Numerical study of effect of operating and design parameters for design of steam reforming reactor. *Energy*, 61, 410–418.
- Kr, M., Chandra, P., & Kr, P. (2015). Journal of Environmental Chemical Engineering A review on the fuel gas cleaning technologies in gasification process, 3, 689–702.
- Kuba, M., Havlik, F., Kirnbauer, F., & Hofbauer, H. (2016). Biomass and Bioenergy Influence of bed material coatings on the water-gas-shift reaction and steam reforming of toluene as tar model compound of biomass gasification, 89, 40–49.
- Langé, S., & Pellegrini, L. a. (2013). Sustainable combined production of hydrogen

- and energy from biomass in Malaysia. *Chemical Engineering Transactions*, 32, 607–612.
- Liu, J. a. (2006). Kinetics , catalysis and mechanism of methane steam reforming. *Worcester Polytechnic Institute, Master The*, 118. Retrieved from <http://scholar.google.com/scholar?hl=en&btnG=Search&q=intitle:Kinetics,+catalysis+and+mechanism+of+methane+steam+reforming#0>
- Liu, Z., Chu, B., Zhai, X., Jin, Y., & Cheng, Y. (2012). Total methanation of syngas to synthetic natural gas over Ni catalyst in a micro-channel reactor. *Fuel*, 95, 599–605.
- Lutz, A. E., Bradshaw, R. W., Bromberg, L., & Rabinovich, A. (2004). Thermodynamic analysis of hydrogen production by partial oxidation reforming. *International Journal of Hydrogen Energy*, 29(8), 809–816.
- Madon, R. H., Fawzi, M., Osman, S. A., Alimin, A. J., Razali, A., Khairul, M., Abeden, Z. Z. (2018). Gas Chromatography Analysis of a C1-C5 Hydrocarbon Column. *International Journal of Integrated Engineering*, 10(1), 85–91.
- Madon, R. H., Mustaffa, N., Fawzi, M., & Osman, S. A. (2015). Review of Yield Intensification on Steam Methane Reforming through Micro Reactor and Rare Earth Catalyst. *Journal of Advanced Review on Scientific Research*, 7(2289–7887), 32–37.
- Madon, R. H., Sarwani, M. K. I., & Fawzi, M. (2016). Effect of substrate surface roughness on morphological and topography of nickel-alumina thin film. *ARPN Journal of Engineering and Applied Sciences*, 11(8), 5304–5308.
- Maluf, S. S., & Assaf, E. M. (2009). Ni catalysts with Mo promoter for methane steam reforming. *Fuel*, 88(9), 1547–1553.
- Marshall, D. W. (2002). *Bench-Scale Design and Testing*. INEEL/EXT-0201018.
- Martin, S., Kraaij, G., Ascher, T., & Wails, D. (2015). An experimental investigation of biodiesel steam reforming. *International Journal of Hydrogen Energy*, 40, 95–105.
- Mathesonrigas. (2010). Basic Flowmeter Principles. Retrieved from www.mathesonrigas.com
- Mbodji, M., Commenge, J. M., & Falk, L. (2014). Preliminary design and simulation of a microstructured reactor for production of synthesis gas by steam methane reforming. *Chemical Engineering Research and Design*, 92(9), 1728–1739.
- Mbodji, M., Commenge, J. M., Falk, L., Di Marco, D., Rossignol, F., Prost, L., Del-

- Gallo, P. (2012). Steam methane reforming reaction process intensification by using a millistructured reactor: Experimental setup and model validation for global kinetic reaction rate estimation. *Chemical Engineering Journal*, 207–208, 871–884.
- Moghtaderi, B. (2007). Effects of controlling parameters on production of hydrogen by catalytic steam gasification of biomass at low temperatures. *Fuel*, 86, 2422–2430.
- Molburg, J. C., & Doctor, R. D. (2003). Hydrogen from Steam-Methane Reforming with CO₂ Capture. *20th Annual International Pittsburgh Coal Conference*, 20.
- Mondal, T., Pant, K. K., & Dalai, A. K. (2015). ScienceDirect Catalytic oxidative steam reforming of bio-ethanol for hydrogen production over Rh promoted Ni / CeO₂ e ZrO₂ catalyst. *International Journal of Hydrogen Energy*, 40(6), 2529–2544.
- Monzon, A., Latorre, N., Ubieto, T., Royo, C., Romeo, E., Villacampa, J. I., Montieux, M. (2006). Improvement of activity and stability of Ni-Mg-Al catalysts by Cu addition during hydrogen production by catalytic decomposition of methane. *Catalysis Today*, 116(3), 264–270.
- Morris, C. C. (2016). Development of A Multi Microchannel Reactor for Steam Methane Reforming Process. *Universiti Tun Hussein Onn Malaysia. Undergraduates Thesis*, (May).
- Murphy, D. M., Manerbino, A., Parker, M., Blasi, J., Kee, R. J., & Sullivan, N. P. (2013). Methane steam reforming in a novel ceramic microchannel reactor. *International Journal of Hydrogen Energy*, 38, 8741–8750.
- Nexant Inc. (2006). Equipment Design and Cost Estimation for Small Modular Biomass Systems , Synthesis Gas Cleanup , and Oxygen Separation Equipment. Task 1: Cost Estimates of Small Modular Systems. *Subcontract Report NREL/SR-510-39943*, (May). Retrieved from <http://www.nrel.gov/docs/fy06osti/39943.pdf>
- Oar-Arteta, L., Wezendonk, T., Sun, X., Kapteijn, F., & Gascon, J. (2017). Metal organic frameworks as precursors for the manufacture of advanced catalytic materials. *Mater. Chem. Front.*, 1, 1709–1745.
- Ogden, J. M. (2001). Review of Small Stationary Reformers for Hydrogen Production. *Environmental Studies*, (609), 63.
- Palma, V., Martino, M., Meloni, E., & Ricca, A. (2017). Novel structured catalysts configuration for intensification of steam reforming of methane. *International*

- Journal of Hydrogen Energy*, 42(3), 1629–1638.
- Park, S., Jung, I., Lee, Y., Kshetrimayum, K. S., Na, J., Park, S., Han, C. (2016). Design of microchannel Fischer – Tropsch reactor using cell-coupling method : Effect of flow configurations and distribution, 143, 63–75.
- Park, S., Yoo, J., Han, S. J., Song, J. H., Lee, E. J., & Song, I. K. (2017). Steam reforming of liquefied natural gas (LNG) for hydrogen production over nickel–boron–alumina xerogel catalyst. *International Journal of Hydrogen Energy*, 42(22), 15096–15106.
- Perez-Moreno, Soler, Herguido, & Menendez. (2013). Stable hydrogen production by methane steam reforming in a two zone fluidized bed reactor: Experimental assessment. *Journal of Power Sources*, 243, 233–241.
- Pirez, C., Fang, W., Capron, M., Paul, S., Jobic, H., Dumeignil, F., & Jalowiecki-Duhamel, L. (2016). Steam reforming, partial oxidation and oxidative steam reforming for hydrogen production from ethanol over cerium nickel based oxyhydride catalyst. *Applied Catalysis A: General*, 518, 78–86.
- Platinum, O., & Catalytic, I. N. (2016). Hetero- / Homogeneous Combustion and Flame Stability of Fuel-Lean Propane – Air Mixtures, 100, 932–943.
- Pudukudy, M., & Yaakob, Z. (2015). Methane decomposition over Ni, Co and Fe based monometallic catalysts supported on sol gel derived SiO₂ microflakes. *Chemical Engineering Journal*, 262, 1009–1021.
- Pudukudy, M., Yaakob, Z., & Akmal, Z. S. (2015). Direct decomposition of methane over SBA-15 supported Ni, Co and Fe based bimetallic catalysts. *Applied Surface Science*, 330, 418–430.
- Radfarnia, H. R., & Iliuta, M. C. (2014). Development of Al-stabilized CaO-nickel hybrid sorbent-catalyst for sorption-enhanced steam methane reforming. *Chemical Engineering Science*, 109, 212–219.
- Rafiq, M. H., & Hustad, J. E. (2011). Synthesis gas from methane by using a plasma-assisted gliding arc catalytic partial oxidation reactor. *Industrial and Engineering Chemistry Research*, 50(9), 5428–5439.
- Rais Hanizam Madon, Mas Fawzi, MZahar, K. I. (2017). IP2017300009. Malaysia: MyIPO.
- Rajagopal, A. (2007). *Preparation And Characterization Of Ni/Rh/Al₂O₃ Catalyst And catalytic Methane-Steam Reforming. Master of Applied Science in Chemical Engineering Thesis*. Royal Military College of Canada :

- Raju, A. S. K., Park, C. S., & Norbeck, J. M. (2009). Synthesis gas production using steam hydrogasification and steam reforming. *Fuel Processing Technology*, 90(2), 330–336.
- Rashad, M., Pan, F., Tang, A., & Asif, M. (2014). Effect of Graphene Nanoplatelets addition on mechanical properties of pure aluminum using a semi-powder method. *Progress in Natural Science: Materials International*, 24(2), 101–108.
- Reinke, M., Mantzaras, J., Bombach, R., Schenker, S., & Inauen, A. (2005). Gas phase chemistry in catalytic combustion of methane/air mixtures over platinum at pressures of 1 to 16 bar. *Combustion and Flame*, 141(4), 448–468.
- Roh, H.-S., Eum, I.-H., & Jeong, D.-W. (2012). Low temperature steam reforming of methane over Ni–Ce(1–x)Zr(x)O₂ catalysts under severe conditions. *Renewable Energy*, 42, 212–216.
- Saadi, S., Hinnemann, B., Appel, C. C., Helveg, S., Abild-pedersen, F., & Nørskov, J. K. (2011). Surface Science First-principles investigations of Ni₃Al (111) and NiAl (110) surfaces at metal dusting conditions, 605, 582–592.
- Salhi, Boulahouache, Petit, Kiennemann, & Rabia. (2011). Steam reforming of methane to syngas over NiAl₂O₄ spinel catalysts. *International Journal of Hydrogen Energy*, 36, 11433–11439.
- Samuel, P. (2003). GTL Technology – Challenge and Opportunities in Catalyst. *Bulletin of The Catalysis Society of India*, 2, 82–99.
- Sarwani, K. I., Madon, R. H., Ibrahim, S. A., & Fawzi, M. (2016). Effect of Calcination Temperature on Morphological and Topography of Nickel-Alumina Thin Film. *MATEC Web of Conferences*, 78, 4–9.
- Sarwani, M. K. I. (2017). Nickel Aluminide Coating as Catalyst in Steam Methane Reforming Microreactor. *Universiti Tun Hussein Onn Malaysia.*, (Master's Thesis).
- Schädel, B. T., Duisberg, M., & Deutschmann, O. (2009). Steam reforming of methane, ethane, propane, butane, and natural gas over a rhodium-based catalyst. *Catalysis Today*, 142, 42–51.
- Sciazko, A., Komatsu, Y., Brus, G., Kimijima, S., & Szmyd, J. S. (2014). A novel approach to the experimental study on methane/steam reforming kinetics using the Orthogonal Least Squares method. *Journal of Power Sources*, 262, 245–254.
- Seider, W.D. Seader, J.D. Lewin, D. R. (2003). *Product and Process Design Principles - Synthesis, Analysis, and Evaluation*. (I. John Wiley and Sons, Ed.) (Second Edi).

New Jersey: Wiley International Edition.

- Seris E.L.C, A. G. (2006). Demonstration PLant For Distributed Production. *Chemical Engineering Research and Design*, 83 (A6)(June 2005), 619–625.
- Shinagawa, T., Oshima, K., & Sekine, Y. (2013). Steam reforming of methane at low temperature in an electric field. *ACS National Meeting Book of Abstracts*, 8, 1.
- Silversand, F. A. (2003). Fuel processor for small-scale production of hydrogen – Experimental study. *Rapport SGC*, 139, 1102–7371.
- Simsek, E., Avci, A. K., & Önsan, Z. I. (2011). Investigation of catalyst performance and microstructured reactor configuration for syngas production by methane steam reforming. *Catalysis Today*, 178(1), 157–163.
- Simsek, E., Karakaya, M., Avci, A. K., & Onsan, Z. I. (2013). Oxidative steam reforming of methane to synthesis gas in microchannel reactors. *International Journal of Hydrogen Energy*, 38, 870–878.
- Smith, R. (2005). *Chemical Process Design and Integration*. (M. Hill, Ed.) (2nd ed.). John Wiley & Sons, Ltd.
- Stefanidis, G. D., & Vlachos, D. G. (2010). Intensification of steam reforming of natural gas: Choosing combustible fuel and reforming catalyst. *Chemical Engineering Science*, 65(1), 398–404.
- Stutz, M. J., Hotz, N., & Poulikakos, D. (2006). Optimization of methane reforming in a microreactor-effects of catalyst loading and geometry. *Chemical Engineering Science*, 61, 4027–4040.
- Sulka, G. D., & J6, P. (2011). Intermetallics Electrochemical behavior of Ni 3 Al-based intermetallic alloys in NaOH, 19, 974–981.
- Tonkovich, a., Kuhlmann, D., Rogers, a., McDaniel, J., Fitzgerald, S., Arora, R., & Yuschak, T. (2005). Microchannel Technology Scale-up to Commercial Capacity. *Chemical Engineering Research and Design*, 83(June), 634–639.
- Tonkovich, a. Y., Perry, S., Wang, Y., Qiu, D., Laplante, T., & Rogers, W. a. (2004). MicroChannel process technology for compact methane steam reforming. *Chemical Engineering Science*, 59, 4819–4824.
- Tonkovich, A. L. Y., Yang, B., Perry, S. T., Fitzgerald, S. P., & Wang, Y. (2007). From seconds to milliseconds to microseconds through tailored microchannel reactor design of a steam methane reformer. *Catalysis Today*, 120, 21–29.
- Türks, D., Mena, H., Armbruster, U., & Martin, A. (2017). Methanation of CO₂ on Ni/Al₂O₃ in a Structured Fixed-Bed Reactor—A Scale-Up Study. *Catalysts*,

7(5), 152–167.

Udengaard, N. (2004). Hydrogen Production by Steam Reforming of Hydrocarbons. *Preprints of Symposia-American Chemical Society*, , 49, 906–907.

Vagia, E. C., & Lemonidou, A. A. (2008). Thermodynamic analysis of hydrogen production via autothermal steam reforming of selected components of aqueous bio-oil fraction. *International Journal of Hydrogen Energy*, 33(10), 2489–2500.

Verykios, & Piga. (2000). *An advanced reactor configuration for the partial oxidation of methane to synthesis gas. Catalysis Today* (Vol. 60).

Vidal Vázquez, F., Simell, P., Pennanen, J., & Lehtonen, J. (2016). Reactor design and catalysts testing for hydrogen production by methanol steam reforming for fuel cells applications. *International Journal of Hydrogen Energy*, 41(2), 924–935.

Wang, F., Qi, B., Wang, G., & Li, L. (2013). Methane steam reforming: Kinetics and modeling over coating catalyst in micro-channel reactor. *International Journal of Hydrogen Energy*, 38, 5693–5704.

Wang, H., Zhang, L., Yuan, M., Xx, T., & Liu, Y. (2012). Steam reforming of ethanol over Ni/Ce_{0.7}Pr_{0.3}O₂ catalyst. *Journal of Rare Earths*, 30(7), 670–675.

Wang, J., Shen, M., Wang, J., Gao, J., Ma, J., & Liu, S. (2012). Steam effects over Pd/Ce_{0.67}Zr_{0.33}O₂-Al₂O₃ three-way catalyst. *Journal of Rare Earths*, 30(3), 748–752.

Wang, Y. (2005). Hydrogen production from steam methane reforming coupled with in situ CO capture: Conceptual parametric study. *Fuel*, 84(14–15), 1778–1789.

Wang, Y., & Chen, W. (2004). Microstructures , properties and high-temperature carburization resistances of HVOF thermal sprayed NiAl intermetallic-based alloy coatings, 183, 18–28.

Wu, H., La Parola, V., Pantaleo, G., Puleo, F., Venezia, A., & Liotta, L. (2013). Ni-Based Catalysts for Low Temperature Methane Steam Reforming: Recent Results on Ni-Au and Comparison with Other Bi-Metallic Systems. *Catalysts*, 3, 563–583.

Wu, Z., & Jiang, H. (2015). Efficient palladium and ruthenium nanocatalysts stabilized by phosphine functionalized ionic liquid for selective hydrogenation. *RSC Advances*, 5(44), 34622–34629.

Xu, J., Yeung, C. M. Y., Ni, J., Meunier, F., Acerbi, N., Fowles, M., & Tsang, S. C. (2008). Methane steam reforming for hydrogen production using low water-ratios without carbon formation over ceria coated Ni catalysts. *Applied Catalysis A:*

General, 345, 119–127.

- Xu, Y., Kameoka, S., Kishida, K., Demura, M., Tsai, A., & Hirano, T. (2005). Catalytic properties of alkali-leached Ni 3 Al for hydrogen production from methanol, *I3*, 151–155.
- Yamada, O. (2006). Generation of hydrogen gas by reforming biomass with superheated steam, *509*, 207–211.
- Yang, H.-C., Lee, M.-W., Hwang, H.-S., Moon, J.-K., & Chung, D.-Y. (2014). Study of cerium-promoted rhodium alumina catalyst as a steam reforming catalyst for treatment of spent solvents. *Journal of Rare Earths*, 32(9), 831–836.
- Ye, G., Xie, D., Qiao, W., Grace, J. R., & Lim, C. J. (2009). Modeling of fluidized bed membrane reactors for hydrogen production from steam methane reforming with Aspen Plus. *International Journal of Hydrogen Energy*, 34(11), 4755–4762.
- Youn, M. H., Seo, J. G., Cho, K. M., Park, S., Park, D. R., Jung, J. C., & Song, I. K. (2008). Hydrogen production by auto-thermal reforming of ethanol over nickel catalysts supported on Ce-modified mesoporous zirconia: Effect of Ce/Zr molar ratio. *International Journal of Hydrogen Energy*, 33(19), 5052–5059.
- Zeppieri, M., Villa, P. L., Verdone, N., Scarsella, M., & De Filippis, P. (2010). Kinetic of methane steam reforming reaction over nickel- and rhodium-based catalysts. *Applied Catalysis A: General*, 387, 147–154.
- Zhai, X., Ding, S., Liu, Z., Jin, Y., & Cheng, Y. (2011). Catalytic performance of Ni catalysts for steam reforming of methane at high space velocity. *International Journal of Hydrogen Energy*, 36, 482–489.
- Zhang, J., Li, X., Chen, H., Qi, M., & Zhang, G. (2017). Hydrogen production by catalytic methane decomposition: Carbon materials as catalysts or catalyst supports. *International Journal of Hydrogen Energy*, 2, 1–21.